








































DIN Type HRC Fuse Links

	SIZE 00	SIZE 1	SIZE 2	SIZE 3
				
REFERENCE				
Voltage Rating	500V AC	500V AC	500V AC	500V AC
Breaking Capacity	100kA	120kA	120kA	80kA
Current Ratings /	4A 	32A 	100A 	315A 
Watt Loss	1.0W	4.6W	10.5W	24.3W
	6A 	36A 	125A 	355A 
	1.0W	5.3W	12.6W	30.0W
	10A 	50A 	200A 	400A 
	1.5W	6.7W	20.6W	32.7W
	16A 	63A 	250A 	500A 
	2.5W	6.5W	21.0W	33.8W
	20A 	80A 	315A 	630A 
	2.6W	9.1W	23.8W	43.5W
	25A 	100A 	400A 	
	2.3W	9.8W	28.3W	
	32A 	125A 		
	3.3W	12.7W		
	40A 	160A 		
	4.0W	16.5W		
	50A 	200A 		
	4.5W	19.8W		
	63A 	250A 		
	5.8W	21.3W		
	80A 			
	6.5W			
	100A 			
	7.4W			
	125A 			
	10.6W			
	160A 			
	10.7W			
Extended Motor Range				
Dimensions (mm)				
Overall Length	78.5	135	150	150
Hole Fixing Centres	BLADE	BLADE	BLADE	BLADE
Diameter	30	48	58	68
Tag Type	CENTRE	CENTRE	CENTRE	CENTRE
No. of Hole Fixing				
Fuse Fittings				
Front Connection	SIZE-00	SIZE-1	SIZE-2	SIZE-3
Busbar Mounting				
Dimensions (mm)				
Length				
Width				
Height				
Comply with	DIN 43620/IEC 269	DIN 43620/IEC 269	DIN 43620/IEC 269	DIN 43620/IEC 269